GRANT SPECIALTY COATINGS
Where Performance Matters

Technical Data Sheet

USA: 103 Main Ave., Elmwood Park, NJ 07407 | (201) 791-8700 | www.grantcoatings.com

GranTex RLM

Thickening Agent

GranTex RLM is a solvent free rheology modifier for inks and coatings. GranTex RLM helps to improve ink transfer in flexographic and gravure printing applications.

Recommended Applications:

- **Flexographic Printing**
- **Gravure Printing**

Compatible Products:

- **Aqueous Resins**
- **Coatings**
- **Finished Inks**

Outstanding Attributes

- Newtonian Viscosity and Non-Shear Thinning.
- Easy to handle and mix.
- Good Water Resistance.
- Excellent Flow and Leveling.

TYPICAL PROPERTIES:	
Appearance	Hazy Viscous Liquid
Specific Gravity	1.04 – 1.05
Solubility	Dilutible in Water
Viscosity	2500 – 3500 cps

HANDLING PRECAUTIONS:

Standard Personal Protection Equipment should be used when handling this material including gloves and safety goggles. Avoid contact with skin or eyes and do not ingest. Use with adequate ventilation and avoid prolonged inhalation of the vapors.

SALES@GRANTCOATINGS.COM

Disclaimer: Although the information is presented in good faith and believed to be correct, Grant Industries makes no representations or warranties as to the completeness or accuracy of Information. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Grant Industries be responsible or liable for any loss of profits, lost goodwill, direct, special, indirect, incidental, or consequential damages of any nature whatsoever, including without limitation lost revenues, resulting from the use of or reliance upon Information or the product to which Information refers. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers.

V06/16